

<b>PRODUCT</b> <b>PRO CORR</b> <b>REDUCERS</b>	
<b>SIZE</b> <b>12" - 48"</b>	<b>MATERIALS</b> <b>V SERIES</b>



### PHYSICAL PIPE DIMENSIONS:

All reducers are comprised of two of the following sizes

Nominal Diameter	ID	OD	Crown Height	Pitch
12"	11.98"	14.62"	1.15"	2.0"
15"	14.96"	17.66"	1.14"	2.67"
18"	17.94"	21.43"	1.46"	3.0"
24"	23.86"	28.01"	1.81"	4.0"
30"	29.86"	34.75"	2.23"	4.0"
36"	35.91"	40.48"	2.26"	3.0"
42"	41.75"	47.27"	2.53"	4.0"
48"	47.96"	54.75"	2.82"	4.0"

### MATERIAL

V Series products are produced with 100% virgin High Density Polyethylene resin meeting the minimum requirements of cell classification of 435400C as described in ASTM D3350.

### SPECIFICATIONS

<b>12" - 24"</b>	AASHTO M330 + ASTM F881/F2736
<b>30" - 48"</b>	AASHTO M330 + ASTM F881

Gaskets, where applicable, shall meet the requirements of:

**ASTM F477 + D3212**