

| | |
|---|-------------------------------------|
| PRODUCT SMOOTH CORR REDUCERS | |
| SIZE 4" - 48" | MATERIALS V SERIES |



PHYSICAL PIPE DIMENSIONS:

All reducers are comprised of two of the following sizes

| Nominal Diameter | ID | OD | Crown Height | Pitch |
|------------------|--------|--------|--------------|--------|
| 4" | 3.99" | 4.70" | 0.295" | 0.647" |
| 6" | 5.99" | 7.01" | 0.455" | 0.65" |
| 8" | 8.1" | 9.49" | 0.636" | 0.97" |
| 10" | 10.07" | 11.79" | 0.730" | 1.33" |
| 12" | 11.98" | 14.62" | 1.15" | 2.0" |
| 15" | 14.96" | 17.66" | 1.14" | 2.67" |
| 18" | 17.94" | 21.43" | 1.46" | 3.0" |
| 24" | 23.86" | 28.01" | 1.81" | 4.0" |
| 30" | 29.96" | 34.75" | 2.23" | 4.0" |
| 36" | 35.91" | 40.48" | 2.26" | 4.7" |
| 42" | 41.75" | 47.27" | 2.53" | 4.7" |
| 48" | 47.96" | 54.75" | 2.82" | 4.7" |

MATERIAL

V Series products are produced with 100% virgin High Density Polyethylene resin meeting the minimum requirements of cell classification of 435400C as described in ASTM D3350.

SPECIFICATIONS

| | |
|--|-----------------------------|
| 4" - 10" | AASHTO M252 + ASTM F667 |
| 12" - 24" | AASHTO M294 + ASTM F2306 |
| 30" - 48" | |
| Gaskets, where applicable, shall meet the requirements of: ASTM F477 + D3212 | |